

Bake & Peel Conductive Foil Tape



P & P Technology "Bake & Peel" tape provides an effective alternative to selective plating or Alocrome on painted enclosures.

The (conductive) adhesive foil tape is fixed in place prior to painting, once painting and baking are completed the peel off mask can be removed to expose a conductive foil surface to which an EMC gasket can be fixed.

Aluminium tapes are held as stock parts, copper and conductive fabric types are available to order.

Part No.	Description	Foil Thickness	Adhesive Thickness	Peel Adhesion	Electrical Resistance
TF-1000	Conductive Aluminium Tape	0.05mm	0.04mm	1075	0.03Ω
TF-1001	Conductive aluminium foil tape.	0.05mm	0.04mm	1020	0.03Ω
TF-1002	Conductive aluminium foil tape.	0.05mm	0.04mm	1060	0.03Ω
TF-1003	Conductive Copper foil tape.	0.05mm	0.04mm	1080	0.03Ω
TF-1004	Conductive fabric tape.	0.093mm	0.04mm	1220	0.03Ω

Temperature specification (baking) 1 hour at 200°C



P & P Technology Ltd
 1 Finch Drive, Springwood
 Braintree, Essex, CM7 2SF, UK
 Tel: +44 (0) 1376 550525 Fax: +44 (0) 01376 552389
 Email: info@p-p-t.co.uk Web: www.p-p-t.co.uk

